

# On the Feasibility of Ontology Debugging via Model Generation

Fabio Papacchini    Renate A. Schmidt

School of Computer Science  
The University of Manchester

August 3, 2015

# What Ontologies are – Example

## Pizza Ontology

$\forall hasTopping. VegetarianTopping \sqsubseteq VegetarianPizza$

$MozzarellaTopping \sqsubseteq VegetarianTopping$

$TomatoTopping \sqsubseteq VegetarianTopping$

$Margherita \sqsubseteq \forall hasTopping. (MozzarellaTopping \sqcup TomatoTopping)$

$Margherita \sqsubseteq \exists hasTopping. MozzarellaTopping$

$Margherita \sqsubseteq \exists hasTopping. TomatoTopping$

$\vdots$

Reasoning on the ontology allows us to derive implicit information such as

$Margherita \sqsubseteq VegetarianPizza$

# Ontology Debugging – Underspecification

## Pizza Ontology

$\forall \text{hasTopping}. \text{VegetarianTopping} \sqsubseteq \text{VegetarianPizza}$

$\text{MozzarellaTopping} \sqsubseteq \text{VegetarianTopping}$

~~$\text{TomatoTopping} \sqsubseteq \text{VegetarianTopping}$~~

$\text{Margherita} \sqsubseteq \forall \text{hasTopping}. (\text{MozzarellaTopping} \sqcup \text{TomatoTopping})$

$\text{Margherita} \sqsubseteq \exists \text{hasTopping}. \text{MozzarellaTopping}$

$\text{Margherita} \sqsubseteq \exists \text{hasTopping}. \text{TomatoTopping}$

⋮

It is no longer true that  $\text{Margherita} \sqsubseteq \text{VegetarianPizza}$

# Our Approach

Use model generation as tests in test-driven software development.

Given an ontology  $\mathcal{O}$  and a set  $S_\alpha$  of properties, check if  $\mathcal{O} \models \alpha$  ( $\mathcal{O} \cup \{\neg\alpha\} \models \perp$ ) for all  $\alpha \in S_\alpha$ .

- if  $\mathcal{O} \not\models \alpha$ 
  - extraction of a model where  $\neg\alpha$  is true
  - the model is an explanation of why  $\mathcal{O} \not\models \alpha$
  - understanding the model allows to fix the ontology
- if  $\mathcal{O} \models \alpha$  then  $\mathcal{O}$  is well specified w.r.t.  $\alpha$

Applicable at any stage of the life cycle of an ontology.

# Our Approach – Example

## Pizza Ontology

$\forall \text{hasTopping}. \text{VegetarianTopping} \sqsubseteq \text{VegetarianPizza}$

$\text{MozzarellaTopping} \sqsubseteq \text{VegetarianTopping}$

~~$\text{TomatoTopping} \sqsubseteq \text{VegetarianTopping}$~~

$\text{Margherita} \sqsubseteq \forall \text{hasTopping}. (\text{MozzarellaTopping} \sqcup \text{TomatoTopping})$

$\text{Margherita} \sqsubseteq \exists \text{hasTopping}. \text{MozzarellaTopping}$

$\text{Margherita} \sqsubseteq \exists \text{hasTopping}. \text{TomatoTopping}$

⋮

Check  $\mathcal{O} \cup \{(\text{Margherita} \sqcap \neg \text{VegetarianPizza})(a)\} \models \perp$

