On computability by logic programs

Andrei Voronkov*
ECRC
Arabellastr.17
8000 Munich 81
Germany
voronkov@ecrc.de

September 4, 1992

Abstract

The problem of computational completeness of Horn clause logic programs is revised. The standard results on representability of all computable predicates by Horn clause logic programs are not related to the real universe on which logic programs operate. For example, SLD-resolution, which is the main mechanism to execute logic programs, may give answers with variables. As the main result we prove that computability by Horn clause logic programs is equivalent to standard computability over the Herbrand universe with variables. The semantics we use is *S-semantics* introduced by Falashi e.a. [2]. As an application of the main result we prove an existence of a metainterpreter for a sublanguage of real Prolog, written in the language of Horn clauses with the S-semantics.

1 Introduction

The statement that Horn clause programs can compute all computable predicates has become folklore in the logic programming literature. However the statement about computational completeness of Horn clauses does not state that Horn clauses can compute all functions on the domain of discourse of Prolog. Whereas Horn clauses operate on the set of all terms in some finite language, the completeness result from [8, 11] is stated for the universe constructed from the constant 0 by repeated applications of the constructor s.

Horn clauses, however, work on arbitrary terms, which can in particular contain variables. The behavior of Horn clauses on such arbitrary terms is complicated due to the use of unification and most general unifiers in the standard operational semantics (SLD-resolution). Thus data types handled by Horn clauses are not only ground terms. It was noted elsewhere that the characterization of logic programs in terms of ground queries is

*On leave from the International Laboratory of Intelligent Systems (SINTEL), 630090, Universitetski Prospect 4, Novosibirsk 90, Russia.

not adequate to its operational semantics [2]. In that paper several semantics were developed so as to capture the inherent property of Horn clauses to compute substitutions.

It is known that some aspects of semantics of Horn clause, for example negation, depend on particular properties of the Herbrand universe [9]. The structure of the Herbrand universe is also important from the computational viewpoint. The proofs of computational completeness of Horn clauses from e.g. [11, 8] cannot be simply modified for the case where the language contains no constants.

The main problem we investigate in this paper is the procedural completeness of Horn clauses on the Herbrand universe in some language. While it is easy to define what are computable functions on such a universe, it is not clear if one can compute them by Horn clause programs. Thus there is a gap between the standard result on procedural completeness of Horn clauses and the real domains on which logic programs operate. In this paper we prove computational completeness of Horn clauses for Herbrand universes with variables.

There are examples of a different behavior of notions of computability on different representations of natural numbers. For example, Minsky's machines [6] simulate all computable functions on a non-standard representation of natural numbers, but do not compute all computable functions on the standard representation. More complicated examples are numerous in the theory of enumerations [1].

In [2] two kinds of semantics to capture domains with variables were defined: one corresponds to the arbitrary Herbrand universes (S-semantics in terms of [2]) and another one to the so called *upward closed* Herbrand universes (C-semantics). Our techniques allows to handle both kinds of semantics. However some applications from section 3 are true only for S-semantics. To give the taste what are these semantics, we introduce some definitions.

We assume that we have a finite set F of function symbols, and to each function symbol $f \in F$ a natural number $n \geq 0$ is assigned (the arity of f). Constants are considered as 0-ary functional symbols. Let $V = v_0, v_1 \ldots$ be an infinite denumerable set of variables.

We assume that the reader is familiar with the basic notions of a substitution, renaming and the most general unifier.

The set *Term* of all terms in the alphabet $\langle F, V \rangle$ is defined as follows:

1. Each variable $v_i \in V$ belongs to *Term*;
2. If f is an $n-$ary function symbol from F, $t_1, \ldots, t_n \in$ *Term*, then $f(t_1, \ldots, t_n) \in$ *Term*.

Via $Term^n$ we denote the set of all tuples $\langle t_1, \ldots, t_n \rangle$ with $t_i \in$ *Term*.

A set $S \subseteq Term^n$ is <u>well-formed</u> iff it is closed under renaming of variables.

We consider semantics of programs in terms of the *computed answer substitutions* [2]. There are at least two possibilities for such a definition. One corresponds to the arbitrary Herbrand universe with variables, and another one corresponds to the *upward-closed* Herbrand universe. They may be characterized as follows. For each Horn clause program $\mathcal{P}$ and each predicate symbol P we introduce two sets:

$$S_{\mathcal{P},P} = \{\langle t_1, \ldots, t_n \rangle \mid \text{For the query } P(x_1, \ldots, x_n) \text{ to the program } \mathcal{P} \text{ SLD-resolution gives an answer substitution } [t_1/x_1, \ldots, t_n/x_n]\}$$

$$C_{\mathcal{P},P} \;=\; \{\langle t_1,\ldots,t_n\rangle \mid \text{For the query } P(t_1,\ldots,t_n) \text{ to the program } \mathcal{P} \text{ SLD-resolution gives the empty answer substitution } []\}$$

The relation between the two semantics can be characterized by the following lemma:

Lemma 1 *Let $\langle t_1,\ldots,t_n\rangle$ be a tuple of terms. Then $\langle t_1,\ldots,t_n\rangle \in C_{\mathcal{P},P}$ iff there exists a tuple of terms $\langle s_1,\ldots,s_n\rangle \in S_{\mathcal{P},P}$ and a substitution θ such that $\langle s_1,\ldots,s_n\rangle\theta = \langle t_1,\ldots,t_n\rangle$.*

Proof. is omitted. ■

It is possible to characterize $S_{\mathcal{P},P}$ in terms of positive hyperresolution [3]. Such a characterization can help in understanding the proofs from this paper.

Lemma 2 *Let $\mathcal{P}$ be a Horn clause program. Then the set $S_{\mathcal{P},P}$ can be defined by the following inductive definitions:*

1. *Each fact from the program $\mathcal{P}$ belongs to $S_{\mathcal{P},P}$.*
2. *The set $S_{\mathcal{P},P}$ is closed under renaming of variables.*
3. *Let atomic formulas $A_1,\ldots,A_n$ belong to $S_{\mathcal{P},P}$ and there is a rule $C\colon -B_1,\ldots,B_n$ in $\mathcal{P}$ such that all variables from A_i are distinct from the variables of A_j and distinct from the variables of $C\colon -B_1,\ldots,B_n$. Let θ be the most general unifier of $A_1,\ldots,A_n$ and $B_1,\ldots,B_n$. Then $C\theta$ belongs to $S_{\mathcal{P},P}$.* ■

Let us give some examples.

In what follows we make the following agreement about the syntax. When displaying concrete Horn clause programs, the variable names start from upper-case letters, while the other symbols start from lower-case letters. However in all other parts of the text we denote variables by x, y, z, u, v, w, possibly with indices.

Example 1 *Below is the program computing the set of pairs*

$$\{\langle t_1, t_2\rangle \mid t_1, t_2 \text{ are two distinct variables}\} :$$

```
distinct_variables(X,Y).
```

Example 2 *Let the set F consists of the constant* `c` *and a binary function symbol* `g`*. The following program computes the set of terms, in which each variable has at most one occurrence:*

```
one_occurrence(X).
one_occurrence(c).
one_occurrence(g(X,Y)) :-
   one_occurrence(X),
   one_occurrence(Y).
```

Example 3 *Let the set F be as in the previous example. The following program computes the set of terms, in which one variable has exactly two occurrences, while all other variables have at most one occurrence:*

```
two_occurrence(T) :-
   two(X,T).

two(X,g(Y,Z)) :-
   one(X,Y),
   one(X,Z).
two(X,g(Y,Z)) :-
   zero(X,Y),
   two(X,Z).
two(X,g(Y,Z)) :-
   two(X,Y),
   zero(X,Z).

one(X,X).
one(X,g(Y,Z)) :-
   one(X,Y),
   zero(X,Z).
one(X,g(Y,Z)) :-
   zero(X,Y),
   one(X,Z).

zero(X,Y).
zero(X,a).
zero(X,g(Y,Z)) :-
   zero(X,Y),
   zero(X,Z).
```

These examples show several interesting features of S-semantics: the set of computed answers $S_{\mathcal{P},P}$ is not closed under substitution (one can easily show this for each of the three programs). The last example also shows that it can be complicated even to express quite simple sets of terms in S-semantics.

2 Main result

We do not assume that the reader is familiar with the theory of recursive functions. The only fact that we use about computability is the characterization of recursively enumerable (computable) predicates given by Matiyaseviĉ (theorem 7 below).

To speak about computability on abstract structures like $Term^n$, one of the possible approaches is to use the notion of enumeration [1]. We encode elements of $Term^n$ by natural numbers. A set of terms is considered computable iff the set of all codes for this set is recursively enumerable (i.e. computable on natural numbers). Let us fix some Gödel numbering γ of $Term^n$ in the following way.

Let $F = \{f_1, \ldots, f_n\}$. Let $p_0, p_1 \ldots$ be the sequence of all prime numbers in increasing order (such that $p_0 = 2, p_1 = 3, \ldots$ etc). Then[1]

$$\gamma(v_i) = 2^i$$

$$\gamma(f_i(t_1, \ldots, t_m)) = 3^i 5^{\gamma(t_1)} \times \ldots \times p_{m+1}^{\gamma(t_m)}$$

Definition 1 *A set $S \subseteq Term^n$ is computable iff the set*

$$\{\langle \gamma(t_1), \ldots, \gamma(t_n)\rangle \mid \langle t_1, \ldots, t_n\rangle \in S\}$$

is recursively enumerable. A relation R is computable if such is the set $\{\langle t_1, \ldots, t_n\rangle \mid R(t_1, \ldots, t_n)\}$.

Now we shall restrict our attention to the S-semantics. At the end of this section we will show how to modify the definitions and the proofs so as to include C-semantics.

Definition 2 *A well-formed set $S \subseteq Term^n$ is H-computable (Horn clause computable) iff $S = S_{\mathcal{P},P}$ for a Horn clause program $\mathcal{P}$ and a predicate symbol P. A relation R is H-computable if such is the set $\{\langle t_1, \ldots, t_n\rangle \mid R(t_1, \ldots, t_n)\}$.*

The main aim of this paper is to show equivalence of the two notions of computability (theorem 15). This theorem states:

A well-formed set $S \in Term^n$ is computable iff it is H-computable.

However the proof is not so easy as for the ground queries. The rest of this section is devoted to the proof of this main result. The proof is quite technical and the reader not interested in technical details may skip the rest of this section.

The proof of the main statement is different from those of [8, 11]. The potential absence of constants makes it mote difficult to simulate computable functions on natural numbers. However it is only a part of the question. In theorem 7 we show how to represent computable functions on natural numbers. The main question is whether we can compute by Horn clause programs all computable functions from the real universe of discourse of Prolog, i.e. Herbrand universe with variables $Term^n$.

The rest of this section is structured as follows. In section 2.1 we consider the most simple case when the language F consists of only constants. In section 2.2 we show how to simulate natural numbers and recursive functions on natural numbers, if F has at least one non-constant. In section 2.3 we consider the case when F contains a function symbol of arity ≥ 2. In this case we can encode lists and substitutions, and prove the main statement using this encoding. In section 2.4 the case of the universe in which all function symbols are unary is considered. In this case we can not encode all substitutions. However it is sufficient to represent substitutions of a fixed length, which proves the main statement for this case.

[1] The mapping γ defined here is not an enumeration in the sense of [1], but it does not matter for our purposes.

2.1 Universe without functions

We start from a simple special case of universes consisting only of constants and variables.

Theorem 3 *Let the set F of function symbols consists only of null-ary symbols, i.e. constants. Then any computable well-formed set $S \subseteq Term^n$ is H-computable.*

Proof. It is easy to see that $Term^n$ has only finite number of elements up to renaming. Thus we can represent them by a Horn clause program consisting only of facts. ■

2.2 Encoding natural numbers

From now on we assume that F contains a function symbol with arity ≥ 1. We fix one such symbol f.

We introduce special pairs of terms called *numerals* to encode natural numbers. For a natural number n the corresponding numeral will be denoted by $\widehat{n}$. More precisely, numerals are equivalence classes of pairs of terms w.r.t. renaming, but for simplicity we shall sometimes use them as just pairs of terms. The definition is as follows:

$$\widehat{0} = \langle v, v \rangle, \text{where } v \in V$$

$$\text{If } \langle t_1, t_2 \rangle = \widehat{n}, \text{then } \langle f(t_1, \ldots, t_1), t_2 \rangle = \widehat{n+1}$$

We denote via ω the tuple of terms $\langle v, f(v, \ldots, v) \rangle$, where v is a variable. The reason to introduce ω and to use such a representation of natural numbers is the following:

Lemma 4 *Let $\langle s_1, s_2 \rangle$ and $\langle t_1, t_2 \rangle$ be numerals.*

1. *The tuples $\langle s_1, s_2 \rangle$ and $\langle t_1, t_2 \rangle$ are unifiable iff $\overline{s_1, s_2} = \overline{t_1, t_2}$. In this case their most general unifier is a renaming substitution.*

2. *The tuple $\langle s_1, s_2 \rangle$ is not unifiable with ω.*

Proof. By routine inspection of the definition of numerals and ω using induction on $\overline{s_1, s_2}$. ■

Lemma 5 *The relation numeral$(t_1, t_2) \rightleftharpoons$ "the pair of terms $\langle t_1, t_2 \rangle$ is a numeral" is H-computable.*

Proof. It is easy to see that the following program computes the relation:

```
numeral(X,X).
numeral(f(X,...,X),Y) :-
   numeral(X,Y). ■
```

Let for a numeral $\langle t_1, t_2 \rangle$ the natural number it encodes is denoted by $\overline{t1, t2}$.

Lemma 6 *The following relations are H-computable:*

1. *zero$(t_1, t_2) \rightleftharpoons \overline{t_1, t_2} = 0$.*

2. *suc$(s_1, s_2, t_1, t_2) \rightleftharpoons \overline{s_1, s_2} + 1 = \overline{t_1, t_2}$;*

3. *plus*$(r_1, r_2, s_1, s_2, t_1, t_2) \rightleftharpoons \overline{r_1, r_2} + \overline{s_1, s_2} = \overline{t_1, t_2}$;

4. *times*$(r_1, r_2, s_1, s_2, t_1, t_2) \rightleftharpoons \overline{r_1, r_2} \times \overline{s_1, s_2} = \overline{t_1, t_2}$;

5. *equal*$(s_1, s_2, t_1, t_2) \rightleftharpoons \overline{s_1, s_2} = \overline{t_1, t_2}$;

Proof. The following program together with the clauses from lemma 5 computes the relations:

```
zero(X,X).

suc(Y1,Y2,f(Y1,...,Y1),Y2) :-
   numeral(Y1,Y2).

plus(X1,X2,Y1,Y2,X1,X2) :-
   zero(Y1,Y2),
   numeral(X1,X2).
plus(X1,X2,Y1,Y2,Z1,Z2) :-
   suc(U1,U2,Y1,Y2),
   suc(V1,V2,Z1,Z2),
   plus(X1,X2,U1,U2,V1,V2).

times(X1,X2,Y1,Y2,Z1,Z2) :-
   zero(Y1,Y2),
   zero(Z1,Z2),
   numeral(X1,X2).
times(X1,X2,Y1,Y2,Z1,Z2) :-
   suc(U1,U2,Y1,Y2),
   times(X1,X2,U1,U2,V1,V2),
   plus(V1,V2,X1,X2,Z1,Z2).

equal(X1,X2,Y1,Y2) :-
   numeral(X1,X2),
   numeral(Y1,Y2),
   eq(X1,Y1),
   eq(X2,Y2).

eq(X,X).
```

To check it one can apply lemma 4. ■

Theorem 7 *Let n be a natural number and R be any recursively enumerable relation on n-tuples of natural numbers. Then the relation $\Re$ on $Term^n$ defined by*

$$\Re(s_1, s_2, \ldots, t_1, t_2) \rightleftharpoons \langle s_1, s_2\rangle, \ldots, \langle t_1, t_2\rangle \text{ are numerals and } R(\overline{s_1, s_2}, \ldots, \overline{t_1, t_2})$$

is H-computable.

Proof. By the theorem proved by Matiyasevič [5] the relation R can be represented in the form

$$R(x_1,\dots,x_n) \rightleftharpoons \exists y_1,\dots,y_k(g(x_1,\dots,x_n,y_1,\dots,y_k)=h(x_1,\dots,x_n,y_1,\dots,y_k)) \qquad (*)$$

where g, h are polynomials (i.e. terms composed only of $0, ', +, \times$. Let *zero, suc, plus, times* be the predicates representing these functions i.e.

$$zero(x) \equiv\ x = 0$$

$$suc(x,y) \equiv\ x' = y$$

$$plus(x,y,z) \equiv\ x + y = z$$

$$times(x,y,z) \equiv\ x \times y = z$$

Using the equivalencies

$$\varphi(0) \equiv\ \exists v(zero(v) \wedge \varphi(v))$$

$$\varphi(s(x)) \equiv\ \exists v(suc(x,v) \wedge \varphi(v))$$

$$\varphi(x+y) \equiv\ \exists v(plus(x,y,v) \wedge \varphi(v))$$

$$\varphi(x \times y) \equiv\ \exists v(times(x,y,v) \wedge \varphi(v))$$

we can rewrite equation $*$ in the form

$$R(v_1,\dots,v_n) \rightleftharpoons \exists v_{n+1},\dots,v_m(\varphi(v_1,\dots,v_m)) \qquad (**)$$

where φ is a conjunction of atomic formulas of one of the following forms: $zero(v_i)$, $suc(v_i,v_j)$, $plus(v_i,v_j,v_k)$, $times(v_i,v_j,v_k)$, $v_i = v_j$, where v_i, v_j, v_k are not necessarily distinct.

We define the translation $\varphi^\star$ of such conjunctions in the following way:

$$(\psi_1 \wedge \psi_2)^\star = \psi_1^\star \wedge \psi_2^\star$$

$$zero(v_i)^\star = \texttt{zero}(v_{2i}, v_{2i+1})$$

$$suc(v_i,v_j)^\star = \texttt{suc}(v_{2i}, v_{2i+1}, v_{2j}, v_{2j+1})$$

$$plus(v_i,v_j,v_k)^\star = \texttt{plus}(v_{2i}, v_{2i+1}, v_{2j}, v_{2j+1}, v_{2k}, v_{2k+1})$$

$$times(v_i,v_j,v_k)^\star = \texttt{times}(v_{2i}, v_{2i+1}, v_{2j}, v_{2j+1}, v_{2k}, v_{2k+1})$$

$$(v_i = v_j)^\star = \texttt{equal}(v_{2i}, v_{2i+1}, v_{2j}, v_{2j+1})$$

Now consider the logic program $\mathcal{P}$, which is obtained from the program from lemma 6 by adding the clause

$\texttt{r}(v_1,\dots,v_{2n})$ `:-` $\varphi^\star(v_1,\dots,v_{2m})$.

By routine inspection of the construction and using lemma 4 one can prove that $\mathtt{r}$ computes R in the program $\mathcal{P}$. ■

Definition 3 *Let $\mathcal{P}$ be a Horn clause logic program and R be a relation on natural numbers. We say that a predicate $\mathtt{r}(X_1, \ldots, X_{2k})$ defined in $\mathcal{P}$ represents R in $\mathcal{P}$ iff for every tuple $t_1, \ldots, t_{2k}$ of terms*

$$\mathtt{r}(t_1, \ldots, t_{2k}) \text{ iff } R(\overline{t_1, t_2}, \ldots, \overline{t_{2k-1}, t_{2k}}).$$

We can reformulate theorem 7 as follows: for every computable predicate R there exist a Horn clause program $\mathcal{P}$ and a predicate $\mathtt{r}$, such that $\mathtt{r}$ represents R in $\mathcal{P}$.

Theorem 7 shows us a way to represent all computable functions on natural numbers by Horn clause logic programs having at least one function symbol in the language. The next step is to show that we can represent the enumeration γ. The technical problem is that we can not distinguish variable numbers in the enumeration γ in programs, because all terms are equivalent up to renaming. The same situation somehow arises in metaprogramming, which is usually solved by encoding variables by terms as in [4]. In practical implementations of Prolog the problem is solved by introducing primitives like `var` or `==`. We will solve this technical problem by introducing "relativized statements"[2] in the subsequent lemmas.

2.3 Universe with a binary function

The proof of the main statement (theorem 15 below) will be different depending on existence of function symbols of arity ≥ 2 in the set F. From now on we assume that g is a fixed function symbol from F with arity 2. (It is easy to change the proof if the arity of g is greater than 2, but we do not want to abuse the notations in this paper). The proof for the case when arity of symbols from F is restricted to 1, will be given below (theorem 14). Let us also note that in general g may coinside with f.

Definition 4 *Let us introduce the notation "term t represent the list of natural numbers $[n_1, \ldots, n_k]$".*

1. *The term $\mathtt{g}(\omega)$ represents the empty list $[]$;*
2. *Let the term t represents the list $[n_1, \ldots, n_k]$, n_0 be a natural number, all the variables of the pair of terms s_1, s_2 be distinct from the variables of t, and $n_0 = \overline{s_1, s_2}$. Then the term $g(g(s_1, s_2), t)$ represents the list $[n_0, \ldots, n_k]$.*

Lemma 8 *The relations*

1. *$R(s)$ — "The term s represents some list of numbers",*
2. *$M(t_1, t_2, s)$ — "The natural number $\overline{t_1, t_2}$ is a member of the list represented by s" and*
3. *$N(t_1, t_2, s)$ — "The natural number $\overline{t_1, t_2}$ is not a member of the list represented by s"*

[2] Statements like "If n is the Gödel number of the variable v, then …

are H-computable.

Proof. By theorem 7 there is a Horn clause program $\mathcal{P}$, which represents the relation "m, n are non-equal natural numbers". Let this relation is computed by the predicate `nonequal(X1,X2,Y1,Y2)`. Consider the program, obtained from $\mathcal{P}$ by adding the definition of `numeral` from lemma 5 and the following clauses:

```
list(g(X,f(X,...,X))).
list(g(g(Y1,Y2),L)) :-
   numeral(Y1,Y2),
   list(L).

member(Y1,Y2,g(g(Y1,Y2),L)) :-
   list(L),
   numeral(Y1,Y2).
member(Y1,Y2,g(g(Z1,Z2),L)) :-
   numeral(Z1,Z2),
   member(Y1,Y2,L)
omega(g(X,f(X,...,X))).

new(Y1,Y2,L) :-
   numeral(Y1,Y2),
   omega(L).
new(Y1,Y2,g(g(Z1,Z2),L)) :-
   nonequal(Y1,Y2,Z1,Z2),
   new(Y1,Y2,L).
```

Using properties of natural numbers and ω from lemma 4, one can prove that `list`, `member`, `new` satisfy the statement of the theorem. ■

Let exponent be any natural number of the form 2^n, assignment be any injective mapping from a finite subset V_0 of the set of variables V to the set of all exponents. Assignments will be denoted by $[x_1/n_1, \ldots, x_k/t_k]$. Whenever we use this notation, we will assume that all variables x_i are pairwise distinct and all numbers n_i are also pairwise distinct.

Definition 5 *Let us introduce the notation "the term t represents the assignment θ".*

1. *The term ω represent the empty assignment $[]$;*
2. *Let the term t represents the assignment $[x_1/t_1, \ldots, x_n/t_n]$, n_0 is an exponent, all the variables of the pair of terms s_1, s_2 are distinct from the variables of t, the variable x_0 does not occur in either of s_1, s_2, t, and $n_0 = \overline{s_1, s_2}$, then the term $g(g(x_0, g(s_1, s_2)), t)$ represents the assignment $[x_0/t_0, x_1/t_1, \ldots, x_n/t_n]$.*

Lemma 9 *The relation $R(t)$ — "The term t represents some assignment" is H-computable.*

Proof. By theorem 7 there is a Horn clause logic program $\mathcal{P}$, which represents the relation "n is an exponent". Let this relation is computed in $\mathcal{P}$ by the predicate `exponent(X1,X2)`. Consider the program, obtained from $\mathcal{P}$ by adding the following clauses:

```
assignment(A) :-
   assignment_aux(A,L).

assignment_aux(A,L) :-
   omega(A),
   omega(L).

assignment_aux(g(g(X,g(Y1,Y2)),A),g(g(Y1,Y2),L)) :-
   assignment_aux(A,L),
   exponent(Y1,Y2),
   list(L),
   new(Y1,Y2,L).
```

To prove that this program computer the relation, it is sufficient to note that the the predicate `assignment_aux` computes the following relation:

> `assignment_aux`$(t,s) \rightleftharpoons$ the term t represents an assignment $[x_1/n_1,\ldots,x_k/n_k]$, and the term s represents the list of numbers $[n_1,\ldots,n_k]$. ■

Let t be a term and all variables of t belong to the set $x_1,\ldots,x_k$. Let θ be an assignment $[x_1/n_1,\ldots,x_k/n_k]$. <u>The Gödel number $\gamma_\theta(t)$ of t under θ</u> is defined similar to the definition of Gödel numbering γ:

$$\gamma_\theta(x_i) = n_i$$

$$\gamma_\theta(f_i(t_1,\ldots,t_m)) = 3^i 5^{\gamma_\theta(t_1)} \times \ldots \times p_{m+1}^{\gamma_\theta(t_m)}$$

Lemma 10 *The following relation $R(t,l,s_1,s_2)$ on terms is H-computable:*

- *the term l represents an assignment $\theta = [x_1/n_1,\ldots,x_k/n_k]$ and*
- *all variables of the term t belong to the set $\{x_1,\ldots,x_k\}$ and*
- *The Gödel number $\gamma_\theta(t)$ of t under the assignment θ is equal to $\overline{s_1,s_2}$.*

<u>Proof.</u> Take the program consisting of the definitions of the relations `assignment_aux`, `new`, `member` , `equal`, `nonequal` and `numeral` from lemmas 5,6,9,8. Add to these program the following:

```
add_to(g(X,g(N1,N2)),A,A) :-
   exponent(N1,N2),
   assignment_aux(A,L),
   member(N1,N2,L),
   glue(g(X,g(N1,N2)),A).
add_to(g(X,g(N1,N2)),A,g(g(X,g(N1,N2)),A)) :-
   exponent(N1,N2),
   assignment_aux(A,L),
   new(N1,N2,L).
```

```
glue(g(X,g(N1,N2)),g(g(X,g(N1,N2)),A)) :-
   numeral(N1,N2).
glue(g(X,g(N1,N2)),g(g(Y,g(M1,M2)),A)) :-
   nonequal(N1,N2,M1,M2),
   glue(g(X,g(N1,N2)),A) :-
```

One can prove the following property of `add_to`: `add_to`$(g(t_1, g(s_1, s_2)), r_1, r_2)$ holds iff

1. t_1 is a variable.
2. r_1, r_2 represent some assignments θ_1, θ_2.
3. One of the following statements is true:
   (a) $t_1/\overline{s_1, s_2} \in \theta_1$ and θ_1 is identical to θ_2;
   (b) $t_1/\overline{s_1, s_2} \notin \theta_1$ and θ_2 is obtained from θ_1 by adding $t_1/\overline{s_1, s_2}$.

Now consider the following clauses:

```
adjoin(A1,A2,A2) :-
   assignment(A2),
   omega(A1).
adjoin(g(g(X,g(N1,N2)),A1),A2,A3) :-
   add_to(g(X,g(N1,N2)),A2,A4),
   adjoin(A1,A4,A3).
```

One can prove the following property of `adjoin`: `adjoin`(t_1, t_2, t_3) is true iff

1. t_1, t_2, t_3 represent assignments $\theta_1, \theta_2, \theta_3$.
2. For a variable v and a natural number n, $v/n \in \theta_3$ iff $v/n \in \theta_1$ or $v/n \in \theta_2$.

Let `f1,...,fn` be all function symbols from F. For each `fi` let $h_i(x_1, \ldots, x_m)$ be the function on natural numbers defined as

$$h(x_1, \ldots, x_m) = 3^i 5^{x_1} \times \ldots \times p_{m+1}^{x_m}$$

(cf. the definition of γ). Let $\mathcal{P}$ be a program such that the predicates `hi(X1,...,X2m)` represent h_i in $\mathcal{P}$. Consider the following clause:

```
gamma(X,L,Y1,Y2) :-
   exponent(Y1,Y2),
   assignment(L1)
   add_to(g(X,g(Y1,Y2)),L1,L).
```

and the clauses

```
gamma(f1(X1,...,Xk),L,Y1,Y2) :-
    gamma(X1,L1,Z1,V1),
    ⋮
    gamma(Xk,Lk,Zk,Vk),
    adjoin(L1,L2,M3),
    adjoin(L3,M3,M4),
    ⋮
    adjoin(Lk,Mk,L),
    hi(Z1,V1,...,Zk,Vk,Y1,Y2).
```

for each `fi` from F.

One can prove the following about `gamma`: `gamma`(s, t, r_1, r_2) holds iff

1. the term t represents an assignment $\theta = [x_1/n_1, \ldots, x_k/n_k]$.
2. the term s is a term all variable of which belong to the set $\{x_1, \ldots, x_k\}$.
3. $\gamma_\theta(s) = \overline{r_1, r_2}$. ■

From this lemma we can prove

Theorem 11 *Let there is at least one symbol with arity* ≥ 2 *in* F. *Then every computable well-formed set* $S \in Term^n$ *is H-computable.*

Proof. Let R be the following set of natural numbers:

$$\{\langle\gamma(s_1), \ldots, \gamma(s_n)\rangle \mid \langle s_1, \ldots, s_n\rangle \in S\}$$

Since R is recursively enumerable, by theorem 7 there exist a Horn clause logic program $\mathcal{P}$ and a predicate `r`, such that `r` represents R in $\mathcal{P}$. Add to the program $\mathcal{P}$ the definition of `gamma` from lemma 10 and the following clause:

```
s(X1,...,Xn) :-
    r(Y1,Z1,...,Yn,Zn)
    gamma(X1,L,Y1,Z1),
    ⋮
    gamma(Xn,L,Yn,Zn).
```

Then

`s`$(t_1, \ldots, t_n) \leftrightarrow$
there are $y_1, z_1, \ldots, y_n, z_n$ and an assignment l, such that l contains all free variables of $t_1, \ldots, t_n$ and for every $i \in \{1, \ldots, n\}$ we have $\gamma_l(t_i) = \overline{y_i, z_i}$ and `r`$(y_1, z_1, \ldots, y_n, z_n) \leftrightarrow$
there are $y_1, z_1, \ldots, y_n, z_n$ and an assignment l, such that l contains all free variables of $t_1, \ldots, t_n$ and for every $i \in \{1, \ldots, n\}$ we have $\gamma_l(t_i) = \overline{y_i, z_i}$ and $\langle\overline{y_1, z_1}, \ldots, \overline{y_n, z_n}\rangle \in R \leftrightarrow$
there is an assignment l, such that l contains all free variables of $t_1, \ldots, t_n$ and $\langle\gamma_l(t_1), \ldots, \gamma_l(t_n)\rangle \in R \leftrightarrow$
$\langle t_1, \ldots, t_n\rangle \in S$.■

2.4 Universe with unary functions

In proving theorem 11 we assumed that there is at least one symbol $g \in F$ of arity ≥ 2. This function symbol g had been used to encode assignments. To represent assignments we needed lists of an arbitrary length, because the number of distinct variables in $Term^n$ is not restricted. Assume now that all function symbols from F have arity 0 or 1. The following lemma gives us a hint how to handle this case.

Lemma 12 *Let all symbols from F have arity 0 or 1. Then any tuple $\tau \in Term^n$ has at most n occurences of variables.* ■

The following lemma is an analog of lemma 10.

Lemma 13 *The following relation $R(x_1, k_1, m_1, \ldots, x_n, k_n, m_n, t, k, m)$ is computable:*

$\langle k_1, m_1 \rangle, \ldots, \langle k_n, m_n \rangle$ *are numerals and*
$x_1, \ldots, x_n$ *are distinct variables and*
$\theta = [x_1/\overline{k_1, m_1}, \ldots, x_n/\overline{k_n, m_n}]$ *is a substitution and*
$\langle k, n \rangle$ *is a numeral and*
$\gamma_\theta(t) = \overline{k, m}.$

Proof. Let `fi`, $i \in \{1, \ldots, l\}$, be all unary function symbols and `fj`, $j \in \{l+1, \ldots, q\}$, be all constants from F. For each `fi` let $h_i(x)$ be the functions on natural numbers defined as

$$hi(x) = \begin{cases} 3^i 5^x, & \text{if } i \leq l \\ 3^i, & \text{if } i > l \end{cases}$$

(cf. the definition of γ). Let $\mathcal{P}$ be a program such that the predicates `hi(X1,...,X2m)` represent h_i in $\mathcal{P}$. Consider the program obtained from $\mathcal{P}$ by adding the following rules.

1. n rules of the form

```
r(X1,M1,K1,...,Xn,Mn,Kn,Xi,Ki,Mi) :-
   exponent(M1,K1),
   ⋮
   exponent(Mn,Kn),
   nonequal(M1,K1,M2,K2),
   nonequal(M1,K1,M3,K3),
   ⋮,
   nonequal(Mn-1,Kn-1,Mn,Kn).
```

   for $i \in \{1, \ldots, n\}$.

2. l rules of the form

```
r(X1,M1,K1,...,Xn,Mn,Kn,fi(T),K,M) :-
   r(X1,M1,K1,...,Xn,Mn,Kn,T,K0,M0),
   hi(k0,m0,K,M).
```

for $i \in \{1, \ldots, l\}$.

3. $q - l$ rules of the form

```
r(X1,M1,K1,...,Xn,Mn,Kn,fi,K,M) :-
   r(X1,M1,K1,...,Xn,Mn,Kn,T,K0,M0),
   hi(K0,M0,K,M).
```

for $i \in \{l+1, \ldots, q\}$.

The proof that r computes R is similar to that of lemma 10. ■

Theorem 14 *Let all function symbols from F have arity 0 or 1. Then any computable well-formed set $S \in Term^n$ is H-computable.*

Proof. is similar to that of theorem 11, but based on lemmas 12 and 13. ■

2.5 Main theorem

Combining theorems 3,11 and 14, we get

Theorem 15 *A well-formed set $S \in Term^n$ is computable iff it is H-computable.*

Proof. In one direction follows from theorems 3,11 and 14. In another direction by standard arguments of theory of recursive functions [7]. ■

It is possible to generalize theorem 15 also to the case of C-semantics. The additions to the above proofs are minor. The major change is the definition of well-formed sets: they should be closed under substitution instead of renaming. All the basic ideas remain the same.

3 An application: metainterpreters

Here we show an application of our results to the problem of constructing *metainterpreters*. One of the interesting questions in comparing two logic programming languages is the existence of a metainterpreter for one logic programming language written in another logic programming language (for a more complete discussion on the subject see e.g. [10]). Metainterpreter for a language may simulate only some aspects of the language's observable behavior. Here we shall show that for S-semantics there is a metainterpreter for a large subset of Prolog written in the language of pure Horn clauses.

Let logic program $\mathcal{P}$ be any finite list $R_1, \ldots, R_k$ of *facts* of the form A and *rules* of the form $A : -A_1, \ldots, A_n$. Assume that the language includes the constant [] and the binary list constructor [|] (we shall use Prolog notations for lists). Let the image $im(A)$ of such a fact be the list [A] and the image $im(A : -A_1, \ldots, A_n)$ of such a rule be the list [$A, A_1, \ldots, A_n$]. We say that the list [$im(R_1), \ldots, im(R_n)$] represents the logic program $\mathcal{P}$ iff for every i, j, if $i \neq j$, then all the variables of $im(R_i)$ are distinct from the variables of $im(R_j)$.

Let us now consider how Prolog works. We do not specify now what variant of the real Prolog we have in mind, since here our considerations are not formal. Given a query q with variables $v_1, \ldots, v_n$ and a program $\mathcal{P}_1$ such that the variables $v_1, \ldots, v_n$ do not occur in $\mathcal{P}_1$, it gives as the result of computations a substitution $v_1 = t_1, \ldots, v_n = t_n$. The answer substitutions may contain variables, these variables must be different from $v_1, \ldots, v_n$ and from all the variables of the program $\mathcal{P}_1$. Let $\mathcal{P}$ be a Horn clause logic program written in a language $\mathcal{L}$. It is called metainterpreter for Prolog iff it defines a ternary predicate `call`, such that $\texttt{call}(t_1, t_2, t_3) \in S_{\mathcal{P},P}$ iff t_3 represents a Prolog program $\mathcal{P}_1$, t_1 is a query to $\mathcal{P}_1$ and t_2 is the answer substitution, computed by Prolog.

Now we restrict ourselves to e.g. standard Prolog with the leftmost choice rule, depth-first computation rule and primitives `!, not, var, ==`.

Theorem 16 *There exist a metainterpreter for Prolog written in the language of pure Horn clauses.*

Proof. Trivially follows from theorem 15. It is sufficient to note that the set

$$\{\texttt{call}(t_1, t_2, t_3) \mid \begin{array}{l} t_3 \text{ represents a Prolog program } \mathcal{P}_1,\ t_1 \text{ is a query to } \mathcal{P}_1 \\ \text{and } t_2 \text{ is an answer substitution computed by Prolog}\} \end{array}$$

is well-formed, i.e. closed under substitution. ∎

It is possible to generalize this theorem to much reacher variants of Prolog. The features that may violate the property to be well-formed are input relations and relations expanding Herbrand universe. Our theorem shows that such strong primitives of Prolog as `var, !` and standard Prolog's choice rule and computation rule do not extend expressive power of Horn clauses, at least at the level of S-semantics. As for C-semantics, the theorem is not true, because the real Prolog is not monotonic. For example, the query `var(t)` gives an answer substitution when `t` is a variable, but fails when `t` is any other term. Thus, we can not capture semantics of real Prolog by C-semantics.

References

[1] Yu.L.Ershov. *Theory of enumerations (in Russian).* Nauka, 1977.

[2] M.Falashi, G.Levi, M.Martelli, and C.Palamidessi. Declarative modeling of the operational behavior of logic languages. *Theoretical Computer Science*, 69(3):298–318, 1989.

[3] L.Henshen and L.Wos. Unit refutation and Horn sets. *Journal of the Association for Computing Machinery*, 21:590–605, 1974.

[4] P.M.Hill and J.W.Lloyd. The Gödel report. Technical Report TR-91-02, Univ. of Bristol, Department of Computer Science, September 1991.

[5] Matiyasevič. The diophantiness of recursively enumerable sets (in Russian). *Soviet Mathematical Doklady*, pages 279–282, 1970.

[6] M.Minsky. *Computation: finite and infinite machines.* Prentice Hall, 1967.

[7] H.Rogers. *Theory of recursive functions and effective computability.* McGraw Hill, 1967.

[8] P. Štěpánek and J.Šebelík. Horn clause programs for recursive functions. In K.L.Clark and S.-Å.Tärnlund, editors, *Logic Programming*, pages 325–340. Academic Press, 1982.

[9] J.C.Sheperdson. Negation in logic programming. In J.Minker, editor, *Deductive Databases and Logic Programming*, pages 19–88. Morgan Kaufmann, 1988.

[10] E.Shapiro. A family of concurrent logic programming languages. *ACM Computing Surveys*, 21(3):412–510, September 1989.

[11] S.-Å. Tärnlund. Horn clause computability. *BIT*, 17:215–216, 1977.